

**Auto Transfer Switch with 2 AC Input Bypass for Loads**

**Features**

- Power bypass to secure power source
- Suitable for video recorders, computers, microwave ovens...etc.
- Two AC INPUTS to supply to AC loads
- Master input and Slave input
- Input source can be generators, inverters, mains, etc.
- Total switching time less than 12 msec
- Switching capacity: 20Amps, 40Amps
- Frequency: 50/60Hz
- Universal output sockets to be plugged in
- Easy understanding LED indicators to display power condition



**Specifications**

Model No.	ATS-20	ATS-40
Rated switched capacity	20A	40A
Maximum switched capacity	40A	80A
<b>Master Input</b>		
Voltage	90-120 volts or 190-240 volts	90-120 volts or 190-240 volts
Frequency	50Hz / 60Hz (Preset)	50Hz / 60Hz (Preset)
<b>Slave Input</b>		
Voltage	0-120 volts or 0-240 volts	0-120 volts or 0-240 volts
Frequency	Not monitored	Not monitored
<b>Thresholds for output of Master</b>		
For switching to Slave	86 volts or 180 volts	86 volts or 180 volts
For switching to Master	90 volts or 188 volts	90 volts or 188 volts
Continuous stability interval	30 sec.	30 sec.
Dimensions (H x W x D) mm	95 x 130 x 240	95 x 130 x 255